

## Specifications

### PopUp WiFi Express

Compact, powerful, high availability WiFi unit with external ethernet port and battery compatibility. Suitable for high volume, high density situations and more remote areas.

#### QUICK FACTS

- Runs using multiple 4G providers at once for increased performance and 99.9% uptime.
- Fibre and Cable WAN compatible.
- CAPTIVATE marketing integration compatible.
- Crowd counting and presence-analytics reporting available. [Quote upon request].
- GPS Tracking available.



#### DIMENSIONS

- 55 x 35 x 23 cm
- 9 kg

#### ROUTER

- Multi-provider capable [2 x Telstra 1 x Optus 1 x Vodafone]
- 400 Mbps throughput
- 8 Load-balancing algorithms
- Static IP capable
- Cloud-managed
- High Gain antennas for superior 4G performance
- VLAN Priority capable
- 1 X Ethernet port for external switching or WAN connectivity
- WiFi WAN compatible

#### POWER

- Powered by standard power Australian outlet
- Battery power available via external 4 pin XLR connector
- Low power consumption [approx. 20-60 watts]
- Compatible with generators

#### ACCESS POINT

- 200 concurrent users
- Latest 802.11AX
- CAPTIVATE compatible
- 4x4 MIMO antenna
- 5Ghz and 2.4Ghz [5Ghz recommended]
- Complies with all major WiFi security standards
- Web content filtering

#### BUILD

- Tough Pelican hard case construction
- Approved to take as carry-on or checked baggage.
- Combination Locked – able to be opened by airport security [TSA approved]
- Splash resistant
- 4-pin XLR power inlet [for battery power]
- Green power indicator light
- External Ethernet – CAT6A for connecting a network switch, direct client access or external WAN