

Specifications

PopUp WiFi Express



www.popup-wifi.com

Compact powerful high availability WiFi unit with external ethernet port and battery compatibility. Suitable for high density situations and more remote areas.

QUICK FACTS

- Runs using three 4G/LTE-Advanced cellular providers concurrently for increased performance and 99.9% uptime.
- CAPTIVATE compatible.
- Crowd counting and presence-analytics compatible.
- Venue permission not required.



DIMENSIONS

- 21.7 x 13.8 x 9 inches
- 23lb

ROUTER

- Multi-provider capable [AT&T, Verizon, T-Mobile]
- 8 Load-balancing algorithms and carrier bonding
- Static public IP address capable
- Cloud-managed
- High-gain antennas for superior 4G performance
- VLAN Priority capable
- 1 X Ethernet port for external switching or WAN connectivity
- WiFi WAN compatible

POWER

- Powered by standard US 3-pin AC power plug
- Battery power available via external 4 pin XLR connector [12V DC]
- Low power consumption [approx. 30 watts]
- Compatible with generators

ACCESS POINT

- 100 concurrent users
- 802.11AX WiFi 6
- CAPTIVATE compatible
- 4x4 MIMO
- 5Ghz and 2.4Ghz [5Ghz recommended]
- Complies with all main WiFi security standards
- Web content filtering

BUILD

- Tough hard case construction
- Approved to take as carry on or checked in luggage
- Combination Locked – able to be opened by airport security [TSA approved]
- Splash resistant
- 4-pin xlr power [for battery power]
- Green power indicator light
- External Ethernet – CAT6A For connecting a network switch, direct client access or external WAN [for battery power]
- Green power indicator light