

Specifications

PopUp WiFi Go

Compact, powerful, high-availability WiFi unit with external ethernet port and battery compatibility.

QUICK FACTS

- Runs two 4G/LTE-Advanced cellular providers concurrently.
- CAPTIVATE compatible.
- Crowd counting and presence analytics compatible.
- GPS Tracking available.
- Not for live video streaming.



DIMENSIONS

- 12.2 x 10.6 x 7.8 in
- 11lb

ROUTER

- Multi-provider capable [AT&T, Verizon, T-Mobile]
- 100Mbps throughput
- 8 Load-balancing algorithms
- Static public IP address capable
- Cloud-managed
- Medium-gain antennas for high 4G performance
- 16 VLANs

POWER

- Powered by standard US 3-pin AC power plug
- Battery power available via external 4 pin XLR connector (12V DC)
- Low power consumption [approx. 20 watts]
- Compatible with generators

ACCESS POINT

- 25 concurrent users
- CAPTIVATE compatible
- 2x2 MIMO
- 5GHz and 2.4GHz (5GHz recommended)
- Complies with all main WiFi security standards
- Web content filtering/application filtering
- Cloud-managed

BUILD

- Rugged hard case construction
- Splash resistant
- Approved to take as carry-on or checked baggage on planes
- Locked, can be opened by airport security [TSA approved]
- 4 pin XLR power inlet to connect to battery power
- Green power indicator light.
- External Ethernet – CAT6A for connecting a network switch, direct client access or external WAN